

# A revolution in hygiene | AP fresh water glasswasher

AP

43 E | 48 E | 53 E | 60 E



43 E



48 E



53 E



60 E



**HOONVED®**



## AP|43 E

AP marks a revolution in glasswashing: outstanding wash results without compromise.

The AP series of professional glasswashers complies with the high quality standards Hoonved is worldwide famous for.

With its Sunrise series Hoonved was the first who introduced on the market the concept of glasswashing with fresh water at all stages of washing and rinsing more than 20 years ago.

## 43 E

AP is unrivalled by other professional glasswashing systems.

The **water pressure** is five times stronger than in the conventional water recycle glasswashers.

The **Steaker Heating Element** placed under the tank:

- allows the heating of the washing water
- optimizes the heating performances
- avoids backdirt

AP is the first glasswasher with an untimed "volumetric" final rinse.

If the main water pressure drops, the AP increases the duration of the rinse cycle ensuring maximum hygiene at the end of the cycle.

## 48 E

## AP|48 E

New design with a double panel housing in stainless steel AISI 304 and a moulded handle.

The **hermetic seal door** assures the perfect thermo-acoustic isolation of the machine.

The **rotating upper and lower wash/rinse systems** in stainless steel are adjustable.

AP|53 E



Digital touch panel control with 4 washing cycles. Wash and rinse temperatures are displayed on the touch panel.

Self diagnosis of machine functioning through alarms.

Adjustable times and washing temperatures on each cycle.

## The only absolute guarantee of cleanliness

Fresh water for every cycle

Impeccable results

Guaranteed temperature of the water during the rinse cycle

Optimized consumption levels

Silent operation

Double panelling

Self-cleaning interior

Easy maintenance

High pressure wash cycle

Induction heating technology

Volumetric rinse cycle for maximum performance

Stops immediately when insufficient water pressure



AP|60 E

AP machines rationalize the use of detergent and rinse aid dosing automatically the required quantity.

Rinse aid pump and detergent pump are standard features on all the models.

60



**HOONVED®**

## Technical specifications



## MODEL

	AP 43 E	AP 48 E	AP 53 E	AP 60 E
Interior	Self-cleaning	Self-cleaning	Self-cleaning	Self-cleaning
Construction	Double skin	Double skin	Double skin	Double skin
Detergent pump	standard	standard	standard	standard
Rinse additive dispenser	standard	standard	standard	standard
Basket	350 x 350 - Ø 360 mm	400 x 400 - Ø 400 mm	450 x 450 mm	500 x 500 mm
Working height	280 mm	280 mm	270 mm	330 mm
Cycle duration (without rinsing)	152/182/242/484 sec.	152/182/242/484 sec.	152/182/242/484 sec.	152/182/242/484 sec.
Water/cycle consumpt.	3,5 - 4 l	3,5 - 4 l	4 - 5 l	5 - 6 l
Boiler capacity	6 l	6 l	7,5 l	7,5 l
Boiler heating element	5000 W	5000 W	6000 W	6000 W
Tank heating element	225 W	225 W	500 W	500 W
Wash pump	400 W	400 W	500 W	500 W
Drain pump	100 W	100 W	100 W	100 W
Total power	5400 W	5400 W	6500 W	6500 W
Electrical connections	400V 3 N 50 Hz	400V 3 N 50 Hz	400V 3 N 50 Hz	400V 3 N 50 Hz
Outlet hose connection	Ø 28 mm	Ø 28 mm	Ø 31 mm	Ø 31 mm
Inlet hose connection	3/4" G (2-4 Bar)	3/4" G (2-4 Bar)	3/4" G (2-4 Bar)	3/4" G (2-4 Bar)

The manufacturer reserves the right to update technical specifications without notice. • Some of the features shown may not be available as standard.

Required hardness of the water supplied between 4° and 10° f (French hardness degrees).

In case of higher levels of hardness, a water softener must be used.

A product – complies with European standards.



Base stand 43|48|53|60 E



Closed base stand |60 E

# HOONVED®



HOONVED-ALI SPA

Via U. Foscolo, 1 • 21040 Venegono Sup. (VA) • Italy • Tel. +39 0331 856 111 • Fax +39 0331 865 223 • e-mail: info@hoonved.com • www.hoonved.com